



## ARC-10W33

### 10.1" WXGA LCD with P-cap Intel® Celeron® N3350 Rugged Touch Panel PC with IET Expansion

- > 10.1" WXGA LCD with PCAP Multi-Touch
- > Onboard Intel® Celeron® N3350 SoC BGA Processor
- > 1 x 204-pin DDR3L SODIMM Socket, Supports Up to 8GB DDR3L 1600MTs SDRAM
- > Rich I/Os, 2 LAN, 2 COM, 4 USB, SIM Card Slot, Swappable Drive Bay, Speaker out for Flexible Expansion Modules
- > 1 x Mini PCIe Slot
- > Rugged Design for Vibration & Shock Protection, Cableless Design
- > Fanless Operation from -10 ~ 50°C
- > Wide Range DC Power Input from +9 ~ 36Vdc
- > Service Window, Easy to Install Memory Module
- > Front panel: IP65, Rear: IP41(except I/O)
- > TPM2.0 (optional)

#### + Spec

System	
<b>Processor</b>	Onboard Intel® Celeron® SoC BGA Processor (Apollo Lake Platform N3350 CPU)
<b>System Memory</b>	One 204-pin DDR3L SODIMM Socket, Supports Up to 8GB DDR3L 1600Mhz SDRAM (Non-ECC)
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec./1sec.step
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>CPU Cooler (Type)</b>	Fanless Heatsink
Expansion	
<b>Expansion</b>	1 x mSATA supports on the 1st Mini PCIe slot, Auto switch for mSATA or Mini PCIe 1 x 80-pin IET interface
Storage	
<b>Storage</b>	1 x 2.5" Drive Bay(7mm HDD Restricted)
<b>HDD/ SSD</b>	1 x SATA3
<b>Other Storage Device</b>	1 x mSATA supports on the 1st Mini PCIe slot, Auto switch for mSATA or Mini PCIe
Panel	
<b>LCD Size</b>	10.1" 16:10
<b>Display Type</b>	WXGA
<b>B/L Inverter/Converter</b>	LCD built in
<b>Resolution</b>	1280x800
<b>Pixel pitch</b>	0.1695mm(H) x 0.1695mm(V)
<b>Luminance</b>	350 cd/m2
<b>Contrast ratio</b>	800
<b>Viewing angle</b>	85 (U), 85 (D), 85 (L), 85 (R)
<b>Response time</b>	25 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	PCAP Multi-Touch support up to 10 points
<b>Touch Light Transmission</b>	88 %
<b>Touch Controller</b>	EETI
I/O	
<b>USB</b>	4 x USB3.0 (2 x Double deck)
<b>COM Port</b>	1 x RS-232/422/485, selectable by BIOS, RS-485 supports Auto Flow, Pin-9 selected by Ring/+5V/+12V) 1 x RS-232
<b>DIO</b>	16-bit GPIO
<b>Expansion</b>	1 x mSATA supports on the 1st Mini PCIe slot, Auto switch for mSATA or Mini PCIe 1 x Optional by IET module
<b>Other</b>	3 x Knockouts for Antenna Mounting
System Control	
<b>LED Indicator</b>	HDD LED, Power LED
Audio	
<b>Chipset</b>	Realtek ALC892
<b>Speaker Output</b>	2 x 2W
Ethernet	
<b>LAN Port</b>	2 x Intel I211AT for APL-M
DC In/Out Characteristics	
<b>Power Type</b>	AT/ATX
Mechanical & Environmental	
<b>Power Requirement</b>	DC +9V ~ +36V, wide voltage single power input TVS component for surge protection Reverse current/voltage protection



<b>Power Type</b>	AT/ATX
<b>Operating Temperature</b>	-10°C ~ 50°C
<b>Storage Temperature</b>	-20°C ~ 60°C
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Weight</b>	2.17Kgs
<b>Mounting Kit</b>	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
<b>Dimension (L x W x H)</b>	282.3 x 201 x 45.8mm
<b>IP Rating</b>	Front Panel IP65 back cover IP41
<b>Vibration Test</b>	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
<b>Shock Test</b>	Operating with SSD/CFast/mSATA : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Die Casting with Cover lens
<b>Construction - Rear</b>	Black Die Casting
<b>Relative Humidity</b>	0~90% Relative Humidity, Non-condensing
<b>Fanless</b>	Yes
<b>Drop</b>	ISTA 2A, IEC-60068-2-32 Test:Ed
<b>Certifications</b>	
<b>Certification Information</b>	CE / FCC Class B
<b>Software Support</b>	
<b>OS Information</b>	Linux, Windows 10
<b>Power Requirement</b>	
<b>Power Connector</b>	Lockable DC Jack (Default) optional for phoenix connector
<b>Power Requirement</b>	DC +9V ~ +36V, wide voltage single power input TVS component for surge protection Reverse current/voltage protection
<b>ACPI</b>	Single power ATX Support S0, S3, S4, S5 and ACPI 3.0 Compliant
<b>Power Mode</b>	AT/ATX
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter



**HY-LINE Computer Components Vertriebs GmbH**

Inselkammerstr. 10 | 82008 Unterhaching

+49 89 / 614 503 40

+49 89 / 614 503 50

computer@hy-line.de

[hy-line-group.com](http://hy-line-group.com)  
LEADER IN TECHNOLOGY.

